



SCOPE

Covers ASTM A135/A795 fire protection pipe with nominal wall thickness as shown. Pipe is intended for new construction and retro fit fire sprinkler systems. Pipe is suitable for roll grooving and welding. Fayette's sprinkler pipe is available in beveled or grooved ends and has a rated working pressure of 300PSI. Produced to the latest version of ASTM A135/A795. All products are UL listed and FM approved.

PRODUCT MARKING

Each length of pipe is continuously stenciled to show the manufacturer, type, length and size.

Each bundle of pipe will have a tag securely attached showing quantity, run #, and dimensions.

DIMENSIONS & WEIGHT

NPS	OD/in.	ID/in.	Nom. Wall Thickness	Empty Wt. (lbs./ft.)	Water Filled Wt. (lbs./ft.)	C.R.R.*	Pieces per Bundle
1	1.315	1.097	.109	1.410	1.800	15.27	91
1-1/4	1.660	1.442	.109	1.810	2.518	9.91	61
1-1/2	1.900	1.682	.109	2.090	3.053	7.76	61
2	2.375	2.157	.109	2.640	4.223	6.27	37
2-1/2	2.875	2.635	.120	3.530	5.893	4.92	30

*Calculated using Standard UL CCR formula, UL Fire Protection Directory, Category VIZY

PRODUCT ASSURANCE

Fayette Pipe Hydro Tests each and every piece of pipe that is produced. We do this to add assurance to the customer that our pipe can be trusted every time it is installed.

- FM Approved
- UL Listed
- Complies with NFPA 13 and 14
- Made from 100% Made and Melted Steel
- NDT Eddy Current Tested
- Hydro Tested

MIC DEFENSE ANTIMICROBIAL COATING

Fayette Pipe applies our Mic Defense coating to all pipe that we manufacture. This coating serves as a protective barrier limiting the opportunity for corrosion from microbiological organisms. The lasting benefits from this coating can be ensured through additional and routine treatment options.

Fayette Pipe
 2282 University Drive
 Lemont Furnace, PA 15456
 724.438.7600
 sales@fayettepipe.com
 www.fayettepipe.com



VETERAN OWNED



MADE IN THE U.S.A.



FAMILY OPERATED